



GROUND LUG SUPPLIED.
TACK WELDED TO INSIDE
WALL OPPOSITE DOOR
FOR EASY ACCESS.

CAST ALUMINUM SQ.
SLIP OVER BASE COVER
WITH 2 SET SCREWS

(2) HEX NUTS AND
(1) WASHER PER
EA. BOLT

3" O.D. TOP 4" O.D. BOTTOM
x .125 WALL TAPERED
ALUMINUM TUBING.

(4 EA) 1/2" DIA.
x 18" LG. GALV.
STEEL ANCHOR BOLTS

CONTINUOUS
WELD

CONCRETE BASE
PER TOWN
STANDARDS

CAST ALUMINUM UPPER
BASE WITH 14 FLUTES.

12-3/8" DIA.
BOLT CIRCLE

10-5/8" SQ.

NOTES:

1. POLE AND LANTERN TO BE FACTORY PAINTED SATIN BLACK UNLESS OTHERWISE SPECIFIED.
2. POLE = HANOVER LANTERN, INC.
DWG. #316-7' THRU 16' OR APPROVED EQUAL.
3. LANTERN = HANOVER LANTERN, INC.
DWG. #L49561 OR APPROVED EQUAL.



TOWN OF WINDSOR
Engineering Department



DECORATIVE LIGHT POLE,
LANTERN, AND BASE

D-402



SCALE: HOR. NTS VER. DATE: AUGUST 2008